SRT VIPER GTS/TA GENERATION 5:

TEAMTECH RAMPAC 6 POINT COMPETITION SEAT BELT INSTALLATION GUIDES









A. B. C.

A. Place Anti-Submarine strap with buckle face down as shown (pad face up). B. Feed staps through seat at point where seat bottom and back come together. C. Flip buckle upright, engage lap buckles as shown.



D. E. F.

D. Remove nuts on rear seat frame, place bar over anchor studs and tighten bar and seat bracket with nuts supplied at each end of bar tighten as per instruction sticker on bar. Wrap Anti-Submarine strap around bar, feed strap back thru 3-bar adjuster, repeat steps with opposite strap as shown in E. F.

Attach snap-hook at end of lap belt to eyebolt as shown, both sides.





G. H.

Place shoulder straps through seat back portals as shown (both sides). Move shoulder pads in to seat back portals as shown in figure H. Take paint scraper, putty knife, or butter knife to gently remove access cover on bulkhead behind seat, locate rubber patches over eyebolt mounting holes inside bulkhead. Place eyebolts in mounting holes, rotate eyebolt until finger tight then finish tightening with a screw driver or similar object. Connect shoulder belts on to eyebolts, move seat back into position and adjust all harnesses to fit occupant's body tightly. Periodically check all fasteners for tightness.

If you should have addition questions or comments you may send an email to curt@teamtechmotorsports.com.